

Smart communications for  
Small Businesses, SoHo and more

# SL2100 Communication System

Cost-effective, feature-rich & VoIP-ready solution with more  
IP technology built-in

**The SL2100 works at a number of levels: a cost-effective VoIP enabled phone system, an easily expanded solution with entry-level unified communications or a reliable TDM based PBX with excellent upgrade potential.**

Much of the technology is built-in reducing the need for extra hardware, licensing and maintenance, all contributing to sharp price point and low running costs.

These features enable the user to meet the demands of today's business including mobility, security, connectivity and ensuring customer service levels are kept at a premium.

As a premises-based system – the SL2100 provides reliability, reducing the risk of downtime.

## Built-in features

- > VoIP enabled
- > Voicemail
- > Music on hold
- > Mobility / Homeworking
- > Auto Attendant
- > Audio Conferencing
- > Video Conferencing & Collaboration (licence required)
- > Call Recording

**“NEC provides further reassurance as a financially stable company with over 100 years technological experience”**



## At a Glance

- > Designed from 4 ports upwards
- > ISDN BRI & PRI/Analogue/SIP trunks
- > Digital/Analogue/IP Extensions
- > On-board Applications
- > Built in features
- > Wall/rack mountable
- > Simple installation
- > Simple operation
- > Highly featured phone functionality



## SL2100 Communication System

| System characteristics      |  |
|-----------------------------|--|
| <b>Chassis dimensions</b>   | 435 x 92.9 x 330 mm / 2.2Kg  |
| <b>Chassis power supply</b> | 90-264 VAC (50/60Hz) 143-182 VA  |
| <b>Compliance</b>           | The SL2100 carries a CE mark and complies with:<br>EMC: EN55032 Emission, EN55024 Immunity, EN61000 Powering Safety: EN60950-1<br>Transmission and signalling: TBR3 (ISDN Basic Rate Access), TBR4 (ISDN Primary Rate Access), TBR8 (ISDN 3.1KHz audio service), ES203-02, TBR38 (Analogue transmission) |


| CPU option                                       | CPU-C1 | CPU-C1-A |
|--|--------|----------|
| Built-In Answering Machine Channel / VRS Channel | 4      | 4        |
| Built-in VRS Messages                            | 100    | 100      |
| Built-in Voicemail Channel                       | 0      | 4        |
| Built-in Voicemail Storage                       | 0      | 2 hours  |
| Built-in IP resources                            | 8      | 8        |
| Built-in SIP trunk licenses                      | 0      | 4        |
| Built-in IP Extension licenses                   | 0      | 4        |

| Number of chassis      |                               | 1   | 2  | 3   |
|------------------------|-------------------------------|-----|----|-----|
| <b>Total Ports</b>     |                               | 240 |    |     |
| <b>Trunk Ports</b>     | Maximum                       | 42  | 84 | 126 |
|                        | Analog                        | 12  | 24 | 36  |
|                        | ISDN BRI                      | 16  | 32 | 48  |
|                        | ISDN PRI                      | 30  | 60 | 90  |
|                        | IP Trunk (SIP/H.323)          | 64  |    |     |
| <b>Extension Ports</b> | Maximum                       | 54  | 92 | 130 |
|                        | Multi-Line Telephone (MLT)    | 24  | 48 | 72  |
|                        | Single Line Telephone (SLT)   | 32  | 64 | 96  |
|                        | IP Terminal (SIP-MLT/Std.)    | 112 |    |     |
|                        | DSS Console-A                 | 3   | 6  | 9   |
|                        | DSS Console-B                 | 12  |    |     |
|                        | Door phone                    | 6   |    |     |
|                        | <b>Virtual Extension Port</b> | 50  |    |     |
| <b>External Paging</b> | 3                             |     |    |     |
| <b>External MOH</b>    | 1                             |     |    |     |
| <b>BGM</b>             | 1                             |     |    |     |
| <b>Door Relay</b>      | 11                            |     |    |     |
| <b>Ethernet Port</b>   | 1                             |     |    |     |
| <b>Analog Modem</b>    | 1                             |     |    |     |

| Category                   | Hardware Name     | Description   | 1 | 2 | 3  |
|----------------------------|-------------------|---|---|---|----|
| <b>System</b>              | IP4WW-Battery Box | External Battery Box  | 1 | 2 | 3  |
|                            | IP7WW-4KSU-C1     | SL2100 Chassis  | 1 | 2 | 3  |
|                            | IP7WW-EXIFE-C1    | Interface card for Expansion Chassis                                  | 0 | 1 | 2  |
| <b>Option Items on CPU</b> | IP7WW-EXIFB-C1    | Interface Card to Expansion Chassis + 16 channel VRS/InMail expansion | 1 | - | -  |
|                            | IP7WW-VOIPDB-C1   | VoIP Resource Expansion Card  | 1 | - | -  |
|                            | IP7WW-SDVMS-C1    | 15 hour voicemail storage expansion                                   | 1 | - | -  |
|                            | IP7WW-SDVML-C1    | 120 hour voicemail storage expansion                                  | 1 | - | -  |
| <b>Expansion Cards</b>     | IP7WW-308U-A1     | 3 Analog Trunks + 8 Hybrid Extensions card.                           | 4 | 8 | 12 |
|                            | IP7WW-082U-B1     | 8 Digital + 2 SLT Extensions card                                     |   |   |    |
|                            | IP7WW-008U-A1     | 8 Hybrid/SLT Extensions card  |   |   |    |
|                            | IP7WW-000U-C1     | 0 Trunk/Extension Card for ISDN BRI/PRI or 3COIDB                     |   |   |    |
|                            | IP7WW-3COIDB-C1   | 3 Analog Trunks Daughter Board  | 4 | 8 | 12 |
|                            | IP7WW-2BRIDB-C1   | 2 ISDN BRI Daughter Board   |   |   |    |
|                            | IP7WW-1PRIDB-C1   | 1 ISDN PRI Daughter Board   |   |   |    |

EMEA (Europe, Middle East, Africa)  
NEC Enterprise Solutions  
[www.nec-enterprise.com](http://www.nec-enterprise.com)

For further information please contact NEC EMEA or:

 **Центр компетенции UNIVERGE®**  
ООО "КУЛТЕЛ"  
125371, г. Москва, 2-ой Тушинский пр-д, 8  
Тел: +7 (916) 947-69-79  
E-mail: [sales@univerge.ru](mailto:sales@univerge.ru)  
Интернет: [www.univerge.ru](http://www.univerge.ru)